



三合一提升机

3-IN-1 lifter

SPEEDLOG 史必诺®

研发制造商

上海史必诺物流设备有限公司

www.speedlog.com.cn

三合一提升机

3-In-1 Lifter

多穿系统的提升机一般位于多穿库区的前端，用于提升货物，和库前输送线进行对接。史必诺自主研发的提升机，可以兼顾提升料箱纸箱和多穿小车车体，多种功能合而为一，能大大减少提升机的数量，降低成本。

The lifter in the multi-shuttle system is typically positioned at the front of the storage area, used to lift goods and interface with the front-end conveyor line.

Speedlog's self-developed lifter is designed to handle both totes/cartons and shuttle carts, combining multiple functions into one unit—significantly reducing the number of lifts required and lowering overall system costs.



料箱提升机产品参数

Specifications of the Box-bin Lifter

匹配料箱尺寸范围 Match the size of carton	400-600mmW * 400-600mmD* 80-400mmH , 可定制 400-600mmW * 400-600mmD* 80-400mmH,it can be customizable		
最大货物载重 Maximum load capacity	0-30kg,50kg以上定制 0-30kg,50kg,it can be customized		
垂直输送速度 Vertical conveying speed	0-120m/min	噪音 Noise	≤75db
提升加速度 Lifting acceleration	0-5m/s ²	总功率 Gross Power	4.5KW
定位精度 Positioning Accuracy	+/-2mm	运行环境温度 Operating ambient temperature	0-45 °C

换层提升机产品参数

Specifications of the Layer Lifter

最大货物载重 Maximum load capacity	200kg	垂直输送速度 Vertical conveying speed	0-60m/min
提升加速度 Layer changing speed	0-5m/s ²	最低首层高度 Minimum first layer height	400mmH
定位精度 Positioning Accuracy	+/-2mm	总功率 Gross Power	5.5KW
运行环境温度 Operating ambient temperature	0-45° C	噪音 Noise	≤75db

上海史必诺物流设备有限公司

Shanghai Speed Logistics Equipment Co., Ltd

Speed up your logistics

咨询热线：800-820-8363 021-51876364

浦东新区浦东南路2240号永业商务楼12楼 邮编：200127

086-21-51876301 FAX:0086-21-51876819 E: info@speedlog.com

ngYe Building, No.2240 South Pudong Road, Pu Dong New District, Shanghai, P.R.China Zip: 200127



微信公众号：SpeedlogGroup

Version:2021.V1.1